

Leydig, Rouse & McCord, Ltd.
700 13th St. N.W., Suite 300, Washington, D.C. 20005

Phone: 202 737-6770

JAW/dml

The Patent Office acknowledges, and has stamped hereon, the date of the receipt of the items checked below:

Docket No.: 401432/M&C

Inventor(s): ALFRED WING KIN CHAN

Title: Pipe Fittings

☒ Transmittal Letter for a
(1 pages; w/duplicate copy)

☒ Rule 53(b) appln ☐ Rule 53(c) provisional appln
☐ §371 national phase appln of PCT/

No. Pages of Spec.: 6 + Abstract

No. Pages of Claims: 1

No. Sheets of Drawings: 2

☒ Application Data Sheet

☒ Return Receipt Postcard

Fee \$ _____

☐ Check ☐ Charged to Deposit Account

☐ Declaration

☐ Associate Power of Attorney

☐ Assignment & Fee

☒ Preliminary Amendment

☐ Priority Document

☐ Information Disclosure Statement

☐ Small Entity Statement(s) ()

☐ PTO-1449 (pages) ☐ & documents

☐
☐

☐

RECEIVED

MAY 22 2003

GROUP 3600



Copy

PATENT
Attorney Docket No. 401432

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

ALFRED WING KIN CHAN

Application No. Unassigned

Art Unit: Unassigned

Filed: October 22, 2001

Examiner: Unassigned

For: PIPE FITTINGS

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D. C. 20231

Dear Sir:

Prior to the examination of the above-identified patent application, please enter the following amendments and consider the following remarks.

IN THE CLAIMS:

Replace the indicated claims with:

1. (Amended) A pipe fitting comprising a hollow body and at least one open end for connection to a pipe, the open end including internal screw threads for connection to a pipe and an integral extension collar which has an inner diameter larger than an internal diameter of the internal screw threads, for surrounding unused trailing screw threads of a pipe connected to the pipe fitting, for forming an annular gap with a pipe connected to the fitting, and for holding a sealing compound, wherein the collar has a wall thickness comparable to the fitting where the internal screw threads are located, and an outer diameter larger than the fitting where the internal screw threads are located.

2. (Amended) The pipe fitting as claimed in claim 1, wherein the screw threads are tapered outwards with respect to an axis of the open end.

3. (Amended) The pipe fitting as claimed in claim 1, made of a galvanised iron material.

RECEIVED
MAY 22 2003
GROUP 3600